

**Ordering Information**

**Drives**  


**Part No. Description**

OEM670T	Torque Servo Drive
OEM670SD	Step and Direction Servo Drive
OEM670X	Servo Drive/Controller
OEM670X-M2	Servo Drive/Controller with battery-backed RAM (2KBytes)

*Use the OEM670 Series with the NeoMetric and J Series motors or "slotted" motors.*

OEM675T	Torque Servo Drive
OEM675SD	Step and Direction Servo Drive
OEM675X	Servo Drive/Controller
OEM675-M2	Servo Drive/Controller with battery-backed RAM (2KBytes)

*Use the OEM675 Series with the SM motors or "slotless" motors.*

**Accessories**  


**Part No. Description**

OEM-HS1*	Heatsink Size 1
OEM-HS2*	Heatsink Size 2
58-013465-01	Thermstrate mounting pad (ordered in multiples of 25)
OEM300	300 Watt peak power output at 75 VDC. Operates at 120 or 240 VAC, 50/60 Hz
OEM1000	1000 Watt peak power output at 70 VDC. Operates at 120 or 240 VAC, 50/60 Hz
OEM1000-Cover	OEM1000 Power Module Cover
M2-KIT	Memory Upgrade Kit (Battery-backed RAM 2 KBytes)

*\* Note: Heatsinks are available for applications with inadequate mounting surface. Whether or not a heatsink is required depends on duty cycle and load characteristics.*

**OEM 670 Motor Compatibility**

The following motors are compatible with the OEM 670 Series drives.

N0701D	J0701D
N0701E	J0701E
N0702E	J0702E
N0702F	J0702F

Please refer to the servo motor section for motor options, specifications, dimensions, and cables.

**OEM 675 Motor Compatibility**

All SM Series and SE Series motors are compatible with the OEM 675 Series drives. Please refer to the servo motor section for motor options, specifications, dimensions, and cables.

**Quality Products Designed and Priced for OEMs and High-Volume Users. Call 1-800-358-9070.**