

Index

- absolute position
 - absolute positioning mode 55
 - absolute zero position 55
 - establishing 55
 - status 55
- acceleration
 - change on the fly 54, 151
 - contouring 126
 - maximum (Following) 192
 - scaling 50
 - s-curve profiling 120
 - units of measure 53, 54
- access to RP240 functions 113
- accuracy
 - Following, factors affecting. 192
 - position capture 85, 155
- address
 - daisy chain (RS-232) 38
 - Ethernet
 - conflict 224
 - multi-drop (RS-485) 41
- advance, geared (Following) ... 178
- alarm events
 - trigger with an input 86
- analog inputs
 - interface 117
 - override voltage 242
- analog output (servos)
 - offset 72
 - setting limits 72
- application examples
 - cam profiling (using compiled
 - Following) 145, 148
 - continuous cut-to-length 187
 - continuous phase shift 177
 - contouring 134
 - electronic gearbox 180
 - multi-tasking 220
 - packaging (using on-the-fly
 - motion) 153
 - PLC 101
 - PLC scan mode 101
 - preset phase shift 178
 - registration 157, 158, 159
 - scaling setup 52
 - servo setup 72
 - spindle (using compiled motion)
 - 143
 - stamping (using compiled
 - Following) 147
 - teaching data points 96
 - trackball 181
 - using a joystick 101
 - using an RP240 101
 - using analog inputs 101
 - using programmable I/O 101
- arc segments 124, 129
- assignment & comparison
 - operators 7
 - used in conditional expressions
 - 25
- assignment of master and following 168
- assumptions, skills required to implement features ii
- axis moving status 228
- axis scaling 48
- axis status 228
 - extended 229
 - relative to Following 198
 - RP240 display 112
- BCD program select input 82
- before you start programming ... iii
- binary value identifier (b) 6
- binary variables (VARB) ... 18, 22
- bit patterns, programmable I/O . 76
- bit select operator (.) 6, 8
- bitwise operations (and, or, not, etc.) 22
- Boolean operations 21
- branching 23
 - conditional 25
 - unconditional 23
- buffers
 - buffered commands
 - control execution of 15
 - executed during motion ... 56, 151
 - stored in a program 9
 - command 56
- C (tangent) axis, contouring... 124, 125, 131
- cam profiling example 145, 148
- capture positions 84
- carriage return, command delimiter 6
- case sensitivity 6
- center specified arcs 130
- change summary i
- characters
 - command delimiters 6
 - comment delimiter 6
 - field separators 6
 - limit per line 6
 - neutral (spaces) 6
- circles 131
- closed-loop operation, steppers.. 64
- COM ports, controlling 37
- commanded direction polarity
 - servos 71
 - steppers 66
- commanded position
 - absolute position reference ... 55
 - follower, tracking error 191
 - status 232
- commands
 - buffer 56
 - after pause 83
 - after stop 83
 - command buffer execution
 - after end-of-travel limit (COMEXL) 15
 - after pause/continue input (COMEXR) 16
 - after stop (COMEXS) 16
 - continuous (COMEXC) 15
 - command value substitutions ... 7
 - delimiters 6
 - errors in programming 237
 - executed during motion 151
 - Following (list of) 200
 - immediate 3, 56
 - restricted execution during
 - motion 17
 - setup command list 44
 - status 228
 - syntax 3
- comment delimiter 6
- communication 35
 - controlling multiple serial ports
 - 37
 - lock port during multi-tasking
 - 214
 - Motion Planner iii
 - options 36
 - problems 224
 - RS-232C daisy-chaining 38
 - RS-485 multi-drop 41
 - via RP240 terminal 107
- compiled motion 136

compare with on-the-fly motion changes	142	C (tangent) axis ...	124, 125, 131	delimiters	
Following profiles.....	139	circles	131	command.....	6
related commands	142	compiling a path	133	comment.....	6
sample applications.....	143, 145, 147, 148	deceleration	126	detecting a stall	64
compiling a contouring path	133	deceleration scaling	51	stall indicator output.....	92
conditional branching	25, 28	defining a path	124	device address	See address
conditional expression examples	25	distance scaling.....	51	direction	
conditional go	159	end points	128	"positive" vs "negative"	53
conditional GO		executing a path.....	133	direction, changes in compiled motion	141
pending trigger input.....	85, 162	conditionally	127	distance	
conditional looping	25, 28	helical interpolation.....	126, 132	calculations, Following	195
conditional path execution	127	line segments	129	compiled motion	140
conditional statement using PMAS	185	local coordinates.....	128	change on the fly	54, 151
configuration		memory allocation	11	registration	155
DAC output limits.....	72	outputs along path	132	units of measure	53, 54
disable drive on kill	48	P (proportional) axis... ..	124, 125, 132	drive	
drive fault level	46	participating axes (PAXES)	125	fault input	
drive resolution	47	programming errors	133	active level (DRFLVL)	46
drive type (AXSDEF)	46	scaling	48	as safety feature.....	100
encoder-based stepper setup ..	64	segment boundary.....	131	enable	46
end-of-travel limits	57	stall condition (stepper axes)	131	status	229
feedback device polarity	70	velocity	126	resolution	47, 225
Following setup	168	velocity scaling.....	51	effect on Following	197
joystick.....	114	work coordinates	128	selection (AXSDEF)	46
memory allocation	11	controlling multiple serial ports.	37	shutdown	
position modes	53	count source (internally generated)		LED status.....	226
programmable inputs	79	170	on kill	48, 83
programmable outputs	90	creating programs	9	stall detection	47
scaling.....	48	DAC output, limiting.....	72	status on RP240.....	113
servo control signal offset.....	72	daisy-chaining	38, 40	dwells & direction changes,	
servo setup	67	with RP240s	41	compiled motion	141
setup commands, list.....	44	data		electrical noise	See installation
setup program	13	fields, in command syntax.....	5	guide	
step pulse (steppers).....	47	read from serial or Ethernet port	26	electronic gearbox application .	180
continuous command execution mode (COMEXC)		read from the RP240.....	26	electronic I/O devices.....	103
effect in continuous positioning mode	56	teach to variable arrays.....	94	electronics concepts	ii
continue		deadband for stall detection.....	64	enable input	
effect on Following motion..	198	debounce time		as safety feature.....	100
continue (!C).....	16, 83	position capture	84	status	230
continue execution on		program select input.....	82	enable or disable Following	173
pause/continue (COMEXR)..	16, 83	programmable inputs.....	81	status	167
83		debugging tools	227	while moving	198
continue execution on stop (COMEXS).....	16, 83	analog input voltages,		encoder	
continue input	83	simulating.....	242	capture/counter enable	
continue key on RP240	107	error messages	234	(steppers).....	65
continuous cut-to-length		I/O activation.....	240	failure detection	66
application	187	identify bad commands	237	status	229
continuous positioning mode	53, 56	problem/cause/solution table	224	feedback for steppers	64
Following.....	174, 194	RP240 menus.....	111	polarity reversal	
distance calculations	195	single-step mode.....	239	servos	70
contouring	124	status commands.....	228	steppers	65
acceleration	126	trace mode	238	position	
acceleration scaling.....	51	deceleration		RP240 display	112
arc segments.....	129	change on the fly	54, 151	resolution	64, 225
		contouring.....	126	setup example	
		scaling	50	servos	72
		s-curve profiling	120	steppers	65
		units of measure.....	53, 54	Z-channel	59
				end point	

- contouring 128
 - linear interpolation 123
- end-of-move settling 74
- end-of-travel limits See limits, end-of-travel
- error
 - clearing 31
 - error handling 30
 - error level for daisy chains 38
 - related to safety 101
 - error message
 - Following specific 199
 - error messages 234
 - Following 191
 - on-the-fly motion errors 152
 - program, assignment 30
 - status 231
- example programs ii
- executing programs... see program, execution options
- expansion I/O 78
- fault output 92
- field separator 6
- filtering, master position See master, master position filtering
- final velocity of a path 126
- follower
 - commanded position 176
 - Following error 191
 - conditional go 159
 - definition of 168
 - distance
 - scaling 172
 - motor/drive accuracy 193
 - move profiles 173
 - ratio to master 172
 - status 167
 - resolution 193
 - scaling 172
 - shift See shift
- following
 - distance
 - move calculations 195
- Following 165
 - cam profiling example . 145, 148
 - commands, list of 200
 - compiled Following profiles 139
 - conditions used in conditional expressions 27
 - distance
 - scaling 51
 - enable or disable 173
 - status 167
 - while moving 198
 - error 191
 - geared advance 178
 - master cycle concept 183
 - maximum acceleration (steppers) 192
 - maximum velocity (steppers) 192
- 192
 - performance considerations. 189
 - prerequisites to Following
 - motion 168
 - ratio Following introduction 166
 - set-up parameters 168
 - status 167, 230
 - technical considerations 189
 - virtual master 170
- geared advance (Following) 178
- general purpose input function .. 81
- general purpose output function 91
- global command identifier (@) ... 6
- GOSUB 23
- GOTO 23
- GOWHEN 159
 - cleared by stop or kill 197
 - error condition 231
 - using PMAS 185
 - using PMAS 198
 - via trigger input 85, 162
- hard limit. See limits, end-of-travel
- helical interpolation 126, 132
- help (tech support services) iv, 243
- hexadecimal value identifier (h). 6, 22
- homing
 - home See limits, home
 - status 228
 - zeroing the absolute position. 59
- host computer operation 118
- I/O activation (simulation) 240
- I/O device interface 102
- IF25
 - using PMAS 185
 - using PMAS 198
- immediate commands 3, 56
 - not stored in programs 9
- immediate data read from RP240 27
- immediate stop 16, 56
- in position, output function 92
- incremental positioning mode ... 55
- inputs
 - analog 117
 - application example 101
 - drive fault 100
 - active level (DRFLVL) 46
 - status 229
 - enable 100
 - status 230
 - encoder See encoder
 - end-of-travel limits .. 56, 57, 100
 - home limits 59
 - joystick 114
 - PLC 103
 - programmable 75, 102
 - alarm event 86
 - bit pattern 76
 - debounce time 81
- end-of-travel limits 89
- function assignments 79, 90
- functions (INFNC), effect on system performance 34
- functions (LIMFNC), effect on system performance .. 34
- general purpose function ... 81
- home limits 89
- jogging 86
- joystick 87
 - kill 56, 83
 - one-to-one program select. 88
 - operand (IN) 25
 - pause/continue 83
 - effect on command buffer 16
 - polarity 81
 - program security 14, 89
 - program select 82
 - simulating activation 240
 - status 80
 - status on RP240 112
 - stop 16, 56, 83
 - update rate 75
 - user fault 84, 100
- stop 16
- thumbwheel 103
- triggers
 - debounce time 81
 - position capture 84
 - programmed functions (TRGFN) 85
 - update rate 75
 - virtual inputs 79
- interface options 101
- interpolation
 - circular/contouring See contouring
 - linear See linear interpolation
- interrupts
 - program (ON conditions) 29
- jerk (acceleration), reducing 120
- jogging
 - input functions 86
 - RP240 jog mode 111
 - setup 86
 - status on RP240 111
- joystick
 - application example 96, 101
 - axis select input 87
 - interface 114
 - problems 226
 - release input 87
 - velocity select input 87
 - voltage override 242
- JUMP 23
- kill
 - assigned input function 83
 - effect on drive 48, 83
 - effect on Following 197

effect on multi-tasking.....	212		
kill on stall	64		
labels (\$).....	23		
last motion segment, compiled			
motion.....	138		
LEDs.....	226		
LEDs on RP240.....	107		
left-to-right math.....	6		
length, master cycle.....	183		
limit to DAC output.....	72		
limits			
end-of-travel	57		
as safety feature	100		
effect on command buffer and			
program execution	15		
programmed functions	89		
status	228		
used as basis to activate			
output.....	92		
home	59		
programmed functions	89		
status on RP240	112		
line feed, command delimiter	6		
line segments	124, 129		
linear interpolation.....	123		
acceleration scaling.....	51		
distance scaling.....	51		
velocity scaling	51		
local coordinate system.....	128		
lockout distance for registration			
.....	156		
logical operators.....	25		
loops			
conditional	27		
unconditional	23		
master			
definition of	168		
status	167		
direction, status of.....	167		
distance			
move calculations	195		
programming (FOLMD) ..	173		
master cycle			
counting	183		
restart	184		
status	183		
length	183		
number.....	185		
position	183		
assignment/comparison		185	
initial.....	184		
rollover.....	183, 198		
status	185		
synchronizing.....	186		
status	167		
master cycle concept.....	183		
master input (A.K.A.).....	166		
master position filtering.....	189, 190		
effect on accuracy	194		
effect on position accuracy			
.....	193		
status.....	167		
master position prediction ..	189,		
190			
effect on accuracy.....	193		
status.....	167		
move profiles.....	173		
moving, status of	167		
ratio to follower.....	172		
status.....	167		
resolution.....	193		
scaling	51, 172		
velocity.....	189		
virtual	170		
master/slave daisy-chain.....	38		
mathematical operations.....	19		
maximum position error			
output to indicate exceeded ..	92		
mechanical cam replacement..	145,		
148			
memory			
allocation	11		
compiled motion.....	136		
contouring.....	124		
locking.....	14, 89		
non-volatile.....	33		
status.....	12		
menus, RP240.....	110		
messages, error	234		
motion			
Following motion status	168		
motion control concepts	ii		
parameters used in conditional			
expressions	25		
pre-compiled profiles	See		
compiled motion			
restrictions while in Following			
.....	198		
rough	199		
synchronize			
conditional GOs.....	159		
registration.....	155		
triggered conditional GOs		159	
triggered start of master cycle			159
with PMAS.....	186		
Motion Planner.....	2		
communication features.....	36		
programming wizards.....	10		
setup program tool.....	13		
move completion criteria.....	74		
moving/not moving status ..	92, 228		
multi-drop, RS-485.....	41		
multiple serial ports, controlling		37	
multi-tasking.....	203		
affected by kill.....	212		
application example.....	220		
conditions used in conditional			
expressions	27		
performance considerations.	218		
programmed I/O functions ..	217		
sharing system resources.....	213		
task identifier (%).....	6, 208, 215		
task-specific resources	215		
negative-direction end-of-travel			
limits	See limit, end-of-travel		
neutral characters	6		
noise, electrical	See installation		
guide			
numeric variables	18		
in conditional expression	25		
NWHILE.....	28		
on conditions (program interrupts)			
.....	29		
effect on system performance		34	
one-to-one program select input.	88		
on-line help for Windows	2		
on-line manuals.....	ii		
on-the-fly motion changes .	54, 151		
compare with compiled motion			
.....	142		
operating system upgrades	243		
operator interface			
host computer operation.....	118		
RP240 remote panel.....	107		
operators			
assignment & comparison.....	7		
correlated to status			
commands	232		
used in conditional			
expressions.....	25		
bit select	8		
bitwise	9		
logic	9		
math	9		
relational	9		
outputs			
activate on position	93		
contouring path	132		
output on position	93		
programmable	75, 102		
bit pattern	76		
fault output	92		
function assignments.....	90		
functions (OUTFNC), effect			
on system performance ..	34		
general purpose function....	91		
limit encountered.....	92		
max position error exceeded			
.....	92		
moving/not moving	92		
operand (OUT).....	25		
output on position.....	93		
polarity	91		
program in progress	92		
simulating activation	240		
stall indicator.....	92		
status	90		
status on RP240.....	112		
update rate	75		

shutdown.....	100	positioning modes	53	programmable	
update rate	75	change on the fly	54, 151	programming	
P (proportional) axis, contouring	124, 125, 132	sampling period.....	189	contouring errors.....	133
participating axes in contouring	125	effect on Following accuracy	193	contouring examples	134
partitioning memory	11	status		creating programs	9
password, RP240	113	RP240 display	112	debug tools.....	227
paths..... See contouring		used to active an output.....	93	debugging via RP240.....	111
pause active, status	230	zeroed after homing.....	59	error messages.....	234
pause key on RP240	107	positive-direction end-of-travel limits..... See limit, end-of-travel		error programs.....	32, 101
pause, effect on Following motion	198	power-up start program (STARTP)	13	examples, using.....	ii
pause/continue input.....	83	clear RP240 menus.....	109	executing programs	
effect on motion & program execution.....	16	Following setup commands.	170	options.....	13
performance, effects on	34	will not execute	226	preparing to program	iii
performance, Following.....	189	prediction of master position..	190.	program example	10
performance, multi-tasking.....	218	See master, master position		program security	89
phase, shift.....	176	prediction		program selection	
PLC interface.....	103	pre-emptive GOs	See on-the-fly	BCD	82
application example.....	101	motion changes		one-to-one	88
PLC scan mode.....	104	preset positioning mode	55	sample programs provided.....	ii
point-to-point move	55	Following	175, 194	scan programs in PLC mode	104
polarity		distance calculations.....	196	set-up program	13, 45
commanded direction		profiling, custom	119	skills required.....	ii
causes reversed direction	225	program		storing programs	11
servos.....	71	branch		proportional axis, contouring ..	124, 125, 132
steppers	66	conditionally.....	25	pulse width.....	47
encoder		unconditionally.....	23	radius specified arcs.....	130
servos.....	70	comments	6	radius tolerance specifications .	129
steppers	65	creating.....	9	ratio of follower to master.....	172
feedback device, servos	70	debug tools	227	status	167
programmable inputs	81	editing in Motion Planner.....	2	reading thumbwheel data	103
programmable outputs	91	error handling.....	30	reference documentation.....	ii
position		error responses	234	registration	155
absolute.....	55	examples, using.....	ii	effect on Following.....	197
establish	55	execution		lockout distance	156
accuracy, Following.....	193	controlling	15	sample application 157, 158, 159	
analog inputs.....	117	from RP240 menu	111	status	156
capture	84	options	13	related documentation.....	ii
commanded.....	65	execution status	230	relational operators	25
encoder	65	flow control	23	REPEAT	25
registration.....	155	interrupts	29	repeatability, Following	
commanded		labels (\$).....	23	position sampling rate	193
capture	84	loop		sensors.....	194
RP240 display.....	112	conditionally.....	25	trigger inputs.....	194
commanded position		unconditionally.....	23	resetting the controller	45
calculation, Following	191	memory allocation.....	11	via the RP240 menu	114
encoder	26	multi-tasking	204	resolution	
capture	84	power-up program	13	drive	47, 225
RP240 display.....	112	program example.....	10	effect on Following.....	197
error	225	programming guidelines.....	1	encoder.....	64, 225
exceeded max. limit		scan programs in PLC mode	104	follower axis	193
status	228	security	14	master axis	193
max. allowable.....	100	setup (configuration) program	13	resources used by multi-tasking	213
RP240 display.....	112	storage	11	responses, error	234
follower axis	176	program in progress.....	92	restart master cycle counting	85, 162, 184
incremental	55	programmable inputs.... See inputs,		restricted commands during	
master	See master	programmable		motion	17
		programmable outputs See outputs,		return procedure.....	243

revision levels from RP240 display	114	single-step mode.....	239	assigned input function	56
revision of this manual.....	i	RP240 menu	111	effect on Following motion..	197
rollover of master cycle position	183, 185, 198	status.....	230	effect on program execution..	16, 83
rough Following motion	199	soft limit ..See limits, end-of-travel		input (INFCi-D)	16
RP240	107	space (neutral character).....	6	stop key on RP240	107
access security	113	stall deadband	64	storing programs in controller	
application example	101	stall detect		memory	11
COM port setup	37, 107	drive.....	47	storing variable data to arrays	94
connectoin verified	230	stall detection.....	64	string variables	18
data read.....	26	stall indicator output.....	92	subroutine, definition of.....	9
front panel description	107	stand-alone operation	101	substitutions, command values.....	7
in daisy chain	41	start-up program (STARTP).....	13	supervisor for multi-tasking	204
menu structure	110	examples for servos	72	support, technical	iv
send text via the connector...	107	include setup parameters	45	swapping tasks	218
RS-232C communication		will not execute	226	synchronizing motion	
daisy-chaining.....	38	statistics, controller config. &		conditional GOs (GOWHEN)	
RP240 connector.....	107	status.....	229	159
RS-485 multi-drop	41	status		Following (follower-to-master)	
runaway motor (servos)	227	absolute position.....	55	186
safety features	100	assigned to binary variable	18	registration	155
sample programs.....	ii	axis		trigger functions	
scaling.....	48, 54	extended	229	conditional GO	162
acceleration & deceleration ..	50	relative to Following	198	start new master cycle	162
distance	51	RP240 display.....	112	syntax	5
effect on system performance	34	command error	237	guidelines	6
follower.....	172	commands		system performance	34
master.....	51, 172	diagnostics related	228	system status	230
velocity	50	list of.....	232	RP240 display	112
scan programs (PLC scan mode)		compiled motion.....	137	system update period.....	189
.....	104	error conditions	231	tangent axis, contouring ..	124, 125, 131
security, program	14, 89	Following	167, 230	target zone.....	74
segment boundary	131	GOWHEN	160	affects moving/not moving	
segment, definition of	11	inputs		output	92
serial ports, controlling	37	enable	230	status (within zone).....	228
servo		RP240 display.....	112	timeout error.....	74
setup.....	67	LEDs	226	status	228
code examples.....	72	limits.....	228	task zero (supervisor).....	204
settling time, actual	74	RP240 display.....	112	tasks	See multi-tasking
set-up commands	44	master cycle number.....	185	teach mode	94
set-up program	13, 45	master cycle position	185	technical considerations for	
shift		motion	25, 228	Following	189
advance	178	OTF profiling conditions.....	152	technical support	iv, 243
continuous.....	176	outputs		terminal emulation	2
application example	177	RP240 display.....	112	testing	
preset.....	176	pause.....	230	program debug tools.....	227
application example	178	position	232	test panels in Motion Planner	
status	167, 176	captured	84	242
<i>shift left to right (>>)</i>	22	RP240 display.....	112	test programs, Motion Planner	2
<i>shift right to left (<<)</i>	22	program execution	230	thumbwheels	103
shutdown.....	100	programmable inputs	80	timeout, target zone.....	74
LED status	226	programmable outputs	90	status	228
on kill.....	48, 83	registration.....	156	trace mode.....	238
SIM modules.....	78	RP240 displays	112	RP240 menu.....	111
simulating analog input voltages		setup parameters	44	status	230
.....	242	statistics	229	trackball application.....	181
sine wave (internally generated)		system.....	230	trigger inputs	
.....	170	RP240 display.....	112	I/O bit pattern	76
single-shot registration.....	156, 158	wait.....	230	position capture	84
		step output pulse width.....	47		
		stop			

